SAFETY DATA SHEET

1. Identification

Product number	1000035108
Product identifier	11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK
Company information	Custom CLS LLC 711 Upland St Chester, PA 19013 United States
Company phone	General Assistance 1-484-483-7530
Emergency telephone US	1-866-836-8855
Version #	01
Recommended use	LUBRICANT
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Gases under pressure	Compressed gas
Health hazards	Carcinogenicity	Category 1B
	Reproductive toxicity (fertility)	Category 2
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger		
Hazard statement	Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause cancer. Suspected of damaging fertility.		
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention.		
Storage	Store locked up. Protect from sunlight. Store in a well-ventilated place.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	Combustible.		
Supplemental information	None.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Dipropylene Glycol Monomethyl Ether		34590-94-8	20 - 40
Methyl Silicone		556-67-2	20 - 40
Carbon Dioxide		124-38-9	10 - 20
Bitumen		8052-42-4	0.1 - 1
Other components below reportab	le levels		20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product name: 11 OZ CUSTOM CLS SI	JPR BOLT & NT LB 24PK	SDS US
Product #: 1000035108 Version #: 01	Issue date: 01-24-2017	1 / 9

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	No specific first aid measures noted.		
Ingestion	Not likely, due to the form of the product.		
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.		
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.		

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2). None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK	SDS US
Product #: 1000035108 Version #: 01 Issue date: 01-24-2017	2/9

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 2 Aerosol.
	Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value		
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	9000 mg/m3	
,		5000 ppm		
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	PEL	600 mg/m3		
		100 ppm		
US. ACGIH Threshold Limit Value	S			
Components	Туре	Value	Form	
Bitumen (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm		
	TWA	5000 ppm		
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	150 ppm		
,	TWA	100 ppm		
US. NIOSH: Pocket Guide to Cher	nical Hazards			
Components	Туре	Value	Form	
Bitumen (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3		
		30000 ppm		
	TWA	9000 mg/m3		
		5000 ppm		
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	900 mg/m3		
,		150 ppm		
	TWA	600 mg/m3		
		100 ppm		

Product name: 11 OZ CUSTOM CLS S	JPR BOLT & NT LB 24PK	SDS US
Product #: 1000035108 Version #: 01	Issue date: 01-24-2017	3 / 9

Components	Туре	Value
Methyl Silicone (CAS 556-67-2)	TWA	10 ppm
ological limit values	No biological exposure limits n	noted for the ingredient(s).
posure guidelines		
US - California OELs: Skir	designation	
Dipropylene Glycol Mor US - Tennessee OELs: Ski		Can be absorbed through the skin.
	nomethyl Ether (CAS 34590-94-8) t Values: Skin designation	Can be absorbed through the skin.
	nomethyl Ether (CAS 34590-94-8) D Chemical Hazards: Skin desig	Can be absorbed through the skin. nation
	nomethyl Ether (CAS 34590-94-8) s for Air Contaminants (29 CFR	Can be absorbed through the skin. 1910.1000)
Dipropylene Glycol Mor	nomethyl Ether (CAS 34590-94-8)	Can be absorbed through the skin.
propriate engineering ntrols	should be matched to condition or other engineering controls to	cally 10 air changes per hour) should be used. Ventilation rates ns. If applicable, use process enclosures, local exhaust ventilation o maintain airborne levels below recommended exposure limits. I established, maintain airborne levels to an acceptable level.
dividual protection measure	s, such as personal protective e	quipment
Eye/face protection	Chemical goggles are recomm	
Skin protection		
Hand protection	Wear appropriate chemical res	sistant gloves. Nitrile gloves are recommended. Suitable gloves c supplier.
Other	Wear suitable protective clothi	ng. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are excee air-supplied respirator.	ded use NIOSH mechanical filter / organic vapor cartridge or an
Thermal hazards	Wear appropriate thermal prot	ective clothing, when necessary.
eneral hygiene nsiderations	personal hygiene measures, s	nce requirements. When using do not smoke. Always observe go uch as washing after handling the material and before eating, utinely wash work clothing and protective equipment to remove

9. Physical and chemical properties

Appearance		
Physical state	Gas.	
Form	Aerosol. Compressed gas.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not available.	
Flash point	311.6 °F (155.3 °C) estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK Product #: 1000035108 Version #: 01 Issue date: 01-24-2017

sds us 4 / 9

Explosive limit - upper (%)	Not available.	
Vapor pressure	Not available.	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Aerosol spray enclosed space		
Deflagration density	1534.65 g/cm3	
Explosive properties	Not explosive.	

Oxidizing properties	Not oxidizing.
Specific gravity	0.845 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Dermal

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be ha	rmful.
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis.	
Information on toxicological ef	fects	
Acute toxicity	May be fatal if swallowed and e	nters airways.
Components	Species	Test Results
Bitumen (CAS 8052-42-4)		
Acute		

LD50	Rabbit	> 2000 mg/kg, 24 Hours		
Inhalation				
LC50	Rat	> 94.4 mg/m3		
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)				
<u>Acute</u>				
Dermal				
LD50	Rabbit	9510 mg/kg, 24 Hours		
		10 ml/kg, 24 Hours		

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK Product #: 1000035108 Version #: 01 Issue date: 01-24-2017 sds us 5 / 9

Components	Species	Test Results
	Rat	> 19020 mg/kg, Hours
		> 20 ml/kg, Hours
Inhalation		
LC50	Rat	> 553 ppm, 8 Hours
		> 275 ppm, 7 Hours
Oral		
LD50	Dog	7.5 ml/kg
	Rat	> 5000 mg/kg
		5.4 ml/kg
Methyl Silicone (CAS 556-67-2)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
		> 2.5 ml/kg
Inhalation		
Aerosol		
LC50	Rat	36 mg/l, 4 Hours
Oral		
LD50	Mouse	1700 mg/kg
	Rat	> 4800 mg/kg
* Estimates for product may b	e based on additional component data r	ot shown.
Skin corrosion/irritation	Prolonged skin contact may cause ten	
Serious eye damage/eye rritation	Direct contact with eyes may cause te	mporary irritation.
Respiratory or skin sensitization	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause	skin sensitization.
Germ cell mutagenicity	No data available to indicate product o mutagenic or genotoxic.	or any components present at greater than 0.1% are
Carcinogenicity	May cause cancer.	
IARC Monographs. Overall	Evaluation of Carcinogenicity	
Bitumen (CAS 8052-42-4 OSHA Specifically Regulate) 2B Po d Substances (29 CFR 1910.1001-105	ssibly carcinogenic to humans. 0)
Not regulated. US. National Toxicology Pro	ogram (NTP) Report on Carcinogens	
Not listed.	- · · · · ·	
Reproductive toxicity	Suspected of damaging fertility.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	

Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful.
12. Ecological information	ו
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.

SDS US

6/9

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK Product #: 1000035108 Version #: 01 Issue date: 01-24-2017

Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation
	potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations


Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

	•	
DO	т	
	UN number	UN1950
	UN proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)
	Transport hazard class(es)	
	Class	2.2
	Subsidiary risk	-
	Label(s)	2.2
	Packing group	Not applicable.
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
IAT	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, non-flammable
	Transport hazard class(es)	
	Class	2.2
	Subsidiary risk	-
	Label(s)	2.2
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	2L
	• •	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.
	Packaging Exceptions	LTD QTY
IMC)G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	A 1	

Class	5	2.2
Subs	idiary risk	-
Labe	l(s)	2.2
Packing	group	Not applicable.
Environm	nental hazards	
Marin	ne pollutant	No.
EmS		Not available.
Special p	recautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packagin	g Exceptions	LTD QTY

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK Product #: 1000035108 Version #: 01 Issue date: 01-24-2017 sds Us 7 / 9



Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Hazard categories **Delayed Hazard - Yes** Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK Product #: 1000035108 Version #: 01 Issue date: 01-24-2017

SDS US 8/9

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))
 - Bitumen (CAS 8052-42-4) Methyl Silicone (CAS 556-67-2)

US. Massachusetts RTK - Substance List

Bitumen (CAS 8052-42-4) Carbon Dioxide (CAS 124-38-9) Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. New Jersey Worker and Community Right-to-Know Act

Bitumen (CAS 8052-42-4) Carbon Dioxide (CAS 124-38-9) Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Bitumen (CAS 8052-42-4) Carbon Dioxide (CAS 124-38-9) Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

01-24-2017
01
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Product and Company Identification: Alternate Trade Names

SDS US

9/9

Product name: 11 OZ CUSTOM CLS SUPR BOLT & NT LB 24PK Product #: 1000035108 Version #: 01 Issue date: 01-24-2017