SAFETY DATA SHEET

1. Identification

Product number	1000035104
Product identifier	15 OZ CUSTM CLS SPR CHN LB LB (2-12)24PK
Company information	Custom CLS LLC 711 Upland St Chester, PA 19013 United States
Company phone	General Assistance 1-484-483-7530
Emergency telephone US	1-866-836-8855
Version #	01
Recommended use	Lubricant
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Sensitization, skin	Category 1
	Specific target organ toxicity, repeated exposure	Category 1
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves.	
Response	If on skin: Wash with plenty of water. Get med irritation or rash occurs: Get medical advice/at	lical advice/attention if you feel unwell. If skin ttention. Wash contaminated clothing before reuse.
Storage	Protect from sunlight. Do not expose to tempe	eratures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations. Hazard(s) not otherwise None known.

classified (HNOC) Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
Propane		74-98-6	10 - 20	
Mineral Spirits		8052-41-3	2.5 - 10	
Cocoyl Diethanolamide		68603-42-9	1 - 2.5	
Solvent Naphtha (Petroleum), Medium Aliphatic		64742-88-7	1 - 2.5	
Diethanolamine		111-42-2	0.1 - 1	
Product name: 15 OZ CUSTM CLS SP	R CHN LB LB (2-12)24PK			SDS US
Product #: 1000035104 Version #: 01 Issue date: 02-20-2017				1/9

Chemical name	Common name and synonyms	CAS number	%
Sulfonic Acids, Petroleum, Calciur Salts	n	61789-86-4	0.1 - 1
Other components below reportab	le levels		60 - 80

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.	
General fire hazards	Extremely flammable aerosol.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

> SDS US 2/9

Product name: 15 OZ CU	JSTM CLS SPR	R CHN LB LB (2-12)24PK
Product #: 1000035104	Version #: 01	Issue date: 02-20-2017

Conditions for safe storage, Level 3 Aerosol. including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	
Mineral Spirits (CAS 8052-41-3)	PEL	2900 mg/m3	
,		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Lin	nit Values		
Components	Туре	Value Form	
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3 Inhalable fraction and vapor.	
Mineral Spirits (CAS 8052-41-3)	TWA	100 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3	
		3 ppm	
Mineral Spirits (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
logical limit values	No biological exposure limits noted for the ingredient(s).		
oosure guidelines			
US - California OELs: Ski	n designation		
Diethanolamine (CAS US ACGIH Threshold Lim	111-42-2) Car it Values: Skin designation	be absorbed through the skin.	
Diethanolamine (CAS	111-42-2) Car	be absorbed through the skin.	
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
ividual protection measure	es, such as personal protective equip	ment	
Eye/face protection	If contact is likely, safety glasses wi	If contact is likely, safety glasses with side shields are recommended.	
Skin protection			
Hand protection	Wear appropriate chemical resistan supplier.	t gloves. Suitable gloves can be recommended by the glove	

Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Product name: 15 OZ CUSTM CLS SPF	R CHN LB LB (2-12)24PK	SDS US
Product #: 1000035104 Version #: 01	Issue date: 02-20-2017	3 / 9

9. Physical and chemical properties

, ,	
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	306.72 °F (152.62 °C) estimated
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	80 - 90 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.802 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materiale	Strong ovidizing agente

incompatible materials	
Hazardous decomposition	

products

Strong usinizing agents.

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.	
Skin contact May cause an allergic skin reaction.		
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Ingestion Expected to be a low ingestion hazard.	
Product name: 15 OZ CUST	TM CLS SPR CHN LB LB (2-12)24PK	SDS US
Product #: 1000035104 Ve	ersion #: 01 Issue date: 02-20-2017	4 / 9

Product #: 1000035104 Version #: 01 Issue date: 02-20-2017

May cause an allergic skin reaction. Dermatitis. Rash.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity	May cause an allergic skin reaction.	
Components	Species	Test Results
Diethanolamine (CAS 111-4	12-2)	
<u>Acute</u>		
Oral		
LD50	Rat	1100 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Solvent Naphtha (Petroleun	n), Medium Aliphatic (CAS 64742-88-7)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Cat	> 6.4 mg/l, 6 Hours
	Rat	> 7.5 mg/l, 6 Hours
		> 4.3 mg/l, 4 Hours
		> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Sulfonic Acids, Petroleum,	Calcium Salts (CAS 61789-86-4)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 4000 mg/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 1.9 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritationProlonged skin contact may cause temporary irritation.Serious eye damage/eyeDirect contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	May cause an allergic skin reaction.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.		
IARC Monographs. Overall	Monographs. Overall Evaluation of Carcinogenicity		
Cocoyl Diethanolamide (Diethanolamine (CAS 11	,	2B Possibly carcinogenic to humans. 2B Possibly carcinogenic to humans.	
Product name: 15 OZ CUSTM CLS SPR CHN LB LB (2-12)24PK Product #: 1000035104 Version #: 01 Issue date: 02-20-2017			sds us 5 / 9

Not regulated. US. National Toxicology Pro Not listed.	ogram (NTP) Report on Carcinogens
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results	
Diethanolamine (CAS 1	11-42-2)			
Aquatic				
Algae	IC50	Algae	7.8 mg/L, 72 Hours	
Crustacea	EC50	Daphnia	55 mg/L, 48 Hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours	
Solvent Naphtha (Petro	leum), Medium Al	iphatic (CAS 64742-88-7)		
Aquatic				
Crustacea	EC50	Daphnia	100.0001 mg/L, 48 Hours	
Daccumulative potential				
Partition coefficient no Diethanolamine	-octanol / water (-1.43		
Mineral Spirits		3.16 - 7.15		
Propane		2.36		
obility in soil	No data a	No data available.		
her adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
B. Disposal conside	rations			
sposal instructions	under pre	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.		

	with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.		

14. Transport information

DOT

UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, flammable, (each not exceeding 1 L capacity)	
Class	2.1	
Product name: 15 OZ CUSTM CLS SPR CHN LB LB (2-12)24PK Product #: 1000035104 Version #: 01 Issue date: 02-20-2017		sds us 6 / 9

Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ

UN number	UN1950		
UN proper shipping name	Aerosols, flammable		
Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Label(s)	2.1		
Packing group	Not applicable.		
Environmental hazards	No.		
ERG Code	10L		
	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.		
Other information			
Passenger and cargo aircraft	Allowed with restrictions.		
Cargo aircraft only	Allowed with restrictions.		
Packaging Exceptions	LTD QTY		
IMDG			
UN number	UN1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Label(s)	2.1		
Packing group	Not applicable.		
Environmental hazards			
Marine pollutant	No.		
EmS	F-D, S-U		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.		
Packaging Exceptions	LTD QTY		
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.		

DOT





Product name: 15 OZ C	USTM CLS SPF	R CHN LB LB (2-12)24PK
Product #: 1000035104	Version #: 01	Issue date: 02-20-2017

sds us 7 / 9 IATA; IMDG



15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.			
TSCA Section 12(b) Export	Notification (40 CFR 707, Su	bpt. D)		
Not regulated.				
CERCLA Hazardous Substa	nce List (40 CFR 302.4)			
Diethanolamine (CAS 111-42-2) Listed.				
SARA 304 Emergency relea	se notification			
Not regulated.				
OSHA Specifically Regulate	d Substances (29 CFR 1910.	.1001-1050)		
Not regulated.				
Superfund Amendments and Re	•	ARA)		
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No			
SARA 302 Extremely hazard	lous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Diethanolamine		111-42-2	0.1 - 1	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutan	ts (HAPs) List		
Diethanolamine (CAS 11 Clean Air Act (CAA) Section	,	Prevention (40 CFR	68.130)	
Propane (CAS 74-98-6)				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. California Controlled Su	ibstances. CA Department o	f Justice (California	a Health and Safety Code Section 1110	0)
Not listed.	-	-	-	-
US. California. Candidate Cl	nemicals List. Safer Consum	er Products Regula	ations (Cal. Code Regs, tit. 22, 69502.3	, subd.

- (a))

Cocoyl Diethanolamide (CAS 68603-42-9) Diethanolamine (CAS 111-42-2) Mineral Spirits (CAS 8052-41-3)

US. Massachusetts RTK - Substance List

Diethanolamine (CAS 111-42-2) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Diethanolamine (CAS 111-42-2) Propane (CAS 74-98-6)

Product name: 15 OZ CUSTM CLS SPR CHN LB LB (2-12)24PK Product #: 1000035104 Version #: 01 Issue date: 02-20-2017 sds us 8 / 9

US. Pennsylvania Worker and Community Right-to-Know Law

Diethanolamine (CAS 111-42-2) Mineral Spirits (CAS 8052-41-3) Propane (CAS 74-98-6)

US. Rhode Island RTK

Diethanolamine (CAS 111-42-2) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2)	Listed: June 22, 2012
Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004
Naphthalene (CAS 91-20-3)	Listed: April 19, 2002

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Version #	02-20-2017 01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Product and Company Identification: Alternate Trade Names

Product name: 15 OZ CUSTM CLS SPR CHN LB LB (2-12)24PK	SDS US
Product #: 1000035104 Version #: 01 Issue date: 02-20-2017	9 / 9